

Technical Accessory Guides (TAGs)

For Associates, Resellers, ISVs and Alliance Partners Global



Version: Active-Only Will only show products that are known to be available for sale

Need to provide an update or change? Contact <u>mailto:pgw786@zebra.com</u>





For Internal Use by PartnerConnect Members Only

Proprietary and Confidential. ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©Zebra Technologies Corp. and/or its affiliates. All rights reserved.

TC8X Series Technical Accessory Guide ZEBRA NOTE: TC8000 discontinued 4/2021 - See PMB 10524 NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection. * Zebra does not endorse or specifically recommend any third-party products, accessories, or hardware. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE. **Cradles and Charging** Single Device Cradles Part Number Picture Description Notes **Required Items** ► Power Supply (PWR-BGA12V50W0WW) ► DC Line Cord (CBL-DC-► Will charge one TC8X and one spare 388A1-01) ► AC Line Cord (23844-00-00F battery ► NOT compatible with Snap-On or country specific version) accessories attached (e.g. audio CRD-TC8X-2SUCHG-01 USB/Charging ShareCradle cables, etc...) USB Cable (25-124330-01R) Not compatible with DPM (Direct Part for PC connection Mark) versions of TC8300. Use CRD-TC8D-2SUCHG-01 instead. Desk Mount Bracket (recommended) 2-Slot Desk Mount Bracket (BRKT-SCRD-SSDK-01) Will charge one TC8X device and one spare battery ► NOT compatible with Snap-On ►AC Line Cord (23844-00-00F accessories attached (e.g. audio or country specific version) cables, etc...) Includes: USB/Charging ShareCradle USB/Charging ShareCradle KT-TC8-01 (CRD-TC8X device-2SUCHG-01), USB Desk Mount Bracket Kit Cable (25-124330-01R), Power Supply (recommended) (PWR-BGA12V50W0WW), and DC Line 2-Slot Desk Mount Bracket Cord (CBL-DC-388A1-01). (BRKT-SCRD-SSDK-01) Not compatible with DPM (Direct Part Mark) versions of TC8300. Use CRD-TC8D-2SUCHG-01 instead. ► Power Supply (PWR-BGA12V50W0WW) ► DC Line Cord (CBL-DC-388A1-01) Only compatible with DPM (Direct Par ► AC Line Cord (23844-00-00F Mark) versions of TC8300. or country specific version) ► Will charge one TC8300 DPM unit an USB/Charging ShareCradle CRD-TC8D-2SUCHG-01 one spare battery. for TC8300 DPM devices ► USB Cable (25-124330-01R) ► NOT compatible with Snap-On for PC connection accessories attached (e.g. audio cables, etc...) Desk Mount Bracket (recommended) 2-Slot Desk Mount Bracket (BRKT-SCRD-SSDK-01)

MOD-MT2-EU1-01		USB to Ethernet Module	 Attaches to USB/Charging ShareCradle (CRD-TC8X-2SUCHG-01) to provide Ethernet support Mechanical switch selects between USB B port and RJ45 Ethernet jack. 10/100/1000 Mbps speed LEDs on module indicate connectivity and speed. NOTE: As of 10/2016 the Ethernet Module hasn't been officially tested by Zebra Engineering with the USB/Charging ShareCradle. 	USB/Charging ShareCradle (CRD-TC8X-2SUCHG-01)
BRKT-SCRD-SSDK-01		Single Device Desk Mount Bracket	 Allows USB/Charging ShareCradle (CRD-TC8X-2SUCHG-01) to be mounted on a flat surface (i.e. desktop). This kit includes pair of stands for Deskplate (BRKT-SCRD-DKST-01) and Deskplate Bracket (BRKT-SCRD-SSPL- 01) - NOTE: Zebra Demo Depot may stock as separate SKU's noted above. 	
Multi-Device Cradles				
Part Number	Picture	Description	Notes	Required Items
CRD-TC8X-5SCHG-01	EEEEE	5-Slot Charge-Only ShareCradle	 Will charge up to five TC8X devices. Not compatible with DPM (Direct Part Mark) versions of TC8300. NOT compatible with Snap-On accessories attached (e.g. audio 	 Power Supply (PWR-BGA12V108W0WW) DC Line Cord (CBL-DC-381A1-01) AC Line Cord (23844-00-00F or country specific version) Mounting Bracket For Desktop: Multi-Slot Desk Mount Bracket
			cables, etc)	(BRKT-SCRD-MSDK-01) For Wall or Network Rack: Multi-Slot Wall/Rack Mount Bracket (BRKT-SCRD-SMRK- 01)

CRD-TC8X-5SETH-01	CURRENT	5-Slot Ethernet/Charging ShareCradle	 Allows speeds up to 1 Gb Will charge and provide Ethernet connection for up to five TC8X devices. NOT compatible with Snap-On accessories attached (e.g. audio cables, etc). Not compatible with DPM (Direct Part Mark) versions of TC8300. 	 Power Supply (PWR- BGA12V108W0WW) DC Line Cord (CBL-DC- 381A1-01) AC Line Cord (23844-00-00F or country specific version) Mounting Bracket For Desktop: Multi-Slot Desk Mount Bracket (BRKT-SCRD-MSDK-01) For Wall or Network Rack: Multi-Slot Wall/Rack Mount Bracket (BRKT-SCRD-SMRK- 01)
CRD-TC8X-5SE4BC-01		4-Slot Ethernet/Charging ShareCradle with Spare Battery Charging	 Allows speeds up to 1 Gb Will charge and provide Ethernet connection for up to four TC8X devices AND will charge four spare batteries NOT compatible with Snap-On accessories attached (e.g. audio cables, etc). Not compatible with DPM (Direct Part Mark) versions of TC8300. 	 Power Supply (PWR- BGA12V108W0WW) DC Line Cord (CBL-DC- 381A1-01) AC Line Cord (23844-00-00F or country specific version) Mounting Bracket For Desktop: Multi-Slot Desk Mount Bracket (BRKT-SCRD-MSDK-01) For Wall or Network Rack: Multi-Slot Wall/Rack Mount Bracket (BRKT-SCRD-SMRK- 01)
BRKT-SCRD-MSDK-01		Multi-Slot Desk Mount Bracket	► Allows Multi-Slot ShareCradles to be mounted on a flat surface (i.e. desktop).	
BRKT-SCRD-SMRK-01		Multi-Slot Wall/Rack Mount Bracket	 Allows for rack and wall mounting of one 5-Slot ShareCradle, up to two 2- Slot Cradles or up to four 4-Slot Battery Chargers. Bracket can be mounted on standard 19" network rack or on a wall. Cable routing slots & removable power supply holder tray. Adjustable tabs & screw mounts for easy hanging/installation with ability to support one 5-Slot ShareCradle or four 4-Slot Battery Chargers and their power supplies. Adjustable orientations - horizontal, vertical, angled. See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	

ADP-TC7X-PLT-FX		Multi-Slot ShareCradle Mounting Bracket Adapter Plate for Honeywell	 Allows Zebra Multi-Slot ShareCradles to be mounted on legacy Honeywell Flex Cradle Wall Mount Brackets (HON SKU #203-641-002). Includes hardware to attach plate to HON wall bracket and secure ShareCradle to plate. NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
Battery Charging	I	I	I	
Part Number	Picture	Description	Notes	Required Items
SAC-TC8X-4SCHG-01		4-Slot Battery Charger	 Charges up to four spare batteries. Can be used standalone or up to four chargers can be installed on Multi-Slot Wall/Rack Mount Bracket (BRKT-SCRD- SMRK-01) 	To power single 4-slot Charger: ▶ Power Supply (PWR- BGA12V50W0WW) ▷ DC Line Cord (CBL-DC-388A1- 01) ▶ AC Line Cord (23844-00-00R or country specific version) To power two sets of 4-slot Chargers from one power supply: ▶ Power Supply (PWR- BGA12V108W0WW) ▷ DC Y-Cable Line Cord (CBL-DC- 523A1-01) ▶ AC Line Cord (23844-00-00R or country specific version)
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-TC8X-USBCHG-01	PL.	Snap-on USB Communication/Charging Cable	 Attaches to rear accessory port on TC8X. Can't be used at same time as other Snap-on accessories 	Eor Charging: ▶ Power Supply (PWR- BUA5V16W0WW), ▶ DC Line Cord (CBL-DC- 383A1-01) ▶ AC Line Cord (50-16000- 182R)
Communication Cables	_			
Part Number	Picture	Description	Notes	Required Items
25-124330-01R	\bigcirc	USB Single-Slot ShareCradle to PC/Host cable	 Micro USB connection on cradle end Cable length is 48 inches 	
CBL-TC8X-USBCHG-01	QL.	Snap-on USB Communication/Charging Cable	 Attaches to rear accessory port on TC8X. Can't be used at same time as other Snap-on accessories 	Eor Charging: ▶ Power Supply (PWR- BUA5V16W0WW), ▶ DC Line Cord (CBL-DC- 383A1-01) ▶ AC Line Cord (50-16000- 182R)

3rd party *		USB micro-A to USB A Female adapter	 Allows the TC8X to act as a USB host to connect to devices like USB flash drives/memory sticks, mice, etc. Connects to Single Device USB/Charge ShareCradle 			
(see http://www.cyberguys.com/product-details/?productid=33062)						
Snap-On Accessories						
Part Number	Picture	Description	Notes	Required Items		
CBL-TC8X-AUDQD-01		Snap-on Audio Adapter (Quick Disconnect jack/connector)	 Allows TC8X to be used with wired headsets with Quick Disconnect jack (i.e. RCH51) For Voice Directed or PTT applications Includes two clips for attaching to clothing. Additional clips can be purchased separately. NOT compatible with other snap on accessories or cradles Cable length is approximately 15 inches (un-extended) 	Compatible headset		
CBL-TC8X-AUDBJ-01		Snap-on Audio Adapter (3.5mm jack)	 Provides 3.5mm barrel jack connector that is keyed/collared for a locking failsafe connection with matching cables and headsets. Not recommended for Voice Directed applications. Use Quick Disconnect cable instead. Can be used with PTT applications. Includes one clip for attaching to clothing. Additional clips can be purchased separately. NOT compatible with other snap on accessories or cradles Cable length is approximately 6 inches (un-extended) Includes Retention/Anti-Rotation Lock (ADP-LOCK-3.5HT1-01) 	Compatible headset		
23-80-09-TSO-A (for Agilion) 23-80-09-TSO-U (for Ubisense) (3rd party) * <u>http://tis-gmbh.de/en</u>		TIS snap-on RTLS Transponder	 Provides Real-Time Location System (RTLS) tracking of the TC8X from various RTLS application providers. Transponder is powered from the TC8X Does not block access to camera. LED on snap-on indicates transponder is being powered. 			
Soft Goods - Cases/Hols	ters	· 	·			
Part Number	Picture	Description	Notes	Required Items		

SG-TC8X-QDHLST-01	Quick-Draw Holster	 Soft material TC8X is inserted nose down into holster Allows easy device insertion and removal. Adjustable orientation allows holster to be wom on left or right side of hip Includes Loop and tether point for optional stylus. Drain hole in case of inclement weather Not compatible with TC8X DPM (Direc Part Mark) configuration devices. Use SG-TC8D-QDHLST-01 instead. 	Belt for Holster (11-08062- 02R)
SG-TC8X-PMHLST-01	Presentation Mode Holster	 Soft material TC8X is inserted handle down into holster Includes Loop and tether point for optional stylus. Holster uses magnet to put TC8X units equiped with proximity sensor into Hands Free Scanning mode. Two storage pockets hold spare batteries. Drain hole in case of inclement weather. Holster can be worn on belt using optional Belt for Holster or can be worn on body using optional Shoulder Strap which attaches to two D-clips on holster. NOTE: Requires TC8X with Proximity/Magnetic Sensor option. Not compatible with DPM (Direct Part Mark) versions of TC8300. 	Belt for Holster (11-08062- 02R) OR Shoulder Strap (WA6010 or 58-40000-007R)

A1214ST (3rd party) *		Holster - Wearable or Fixed Mount	 Durable Ballistic Nylon Holster. Covered Belt Clip for quick on/off waist belt. Grommetted holes for fixed mounting. Includes two plastic cable tie-wraps. Includes loop on front for optional retractor for attachment to TC8X. Grommetted hole at bottom for easy in/out of unit and drainage. Stiffeners for structure and rigidity. Can be used with optional Waist Belt for Holster (A1227ST) 	
AE2449DW (3rd party) * http://www.ultimacase.com		Boot with Cell Phone Clip and D-Ring	 Buckled strap at bottom for quick on/off. Can be used on fork-lifts by using D- Ring at top of boot for attaching a pulley/ retractor. Can be worn on belt using rugged cel clip which allows for quick user attachment. 	Use Tool Balancer/Pulley (50- 15400-031) when attaching to forklifts.
11-08062-02R	Ŷ	Belt for Holster	 Belt is 2 inches wide Extends to 48 inches Has improved buckle and softer belt material 	
A1227ST (3rd party) * <u>https://www.shilpitrading.com</u>		Belt for Holster	 Belt is 2 inches wide Extends to 48 inches Quick on/off snap buckle 	
V6198DW (3rd party) * http://www.ultimacase.com		Belt Extender	► Used to extend the Belt Holster (11- 08062-02R) an additional 10 inches	
58-40000-007R	Į J	Shoulder Strap/Cross Body Strap	▶1.5" wide, 22 to 50" max. length	
Misc				

Part Number	Picture	Description	Notes	Required Items
SG-TC7X-STYLUS1-03 (pack of 3) SG-TC5X-STYLUS-50 (pack of 50) NOTE: 50-pack is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.		Stylus	 Conductive Carbon-filled plastic material w/ 5mm tip. Length of stylus is 3.5". Rigid plastic stylus is optimized for enterprise durability. Clip & tether point to reduce loss. When not being used stylus can be stored in optional Holster 	
SG-TC7X-STYLUS-03 (pack of 3) SG-TC7X-STYLUS-06 (pack of 6) NOTE: 6-pack is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	ļ	Stylus Kit with Tether	 Includes fine-pitch, capacitive Stylus (SG-TC7X-STYLUS1-03) and coiled tether (KT-TC7X-TETHR1-03) Conductive Carbon-filled plastic material w/ 5mm tip. Length of stylus is 3.5". Rigid plastic stylus is optimized for enterprise durability. Clip & tether point to reduce loss. Tether to optional Handstrap When not being used stylus can be stored in optional Holster 	
SG-STYLUS-TCX-MTL-03 (pack of 3)		Fiber Tipped Stylus	 Black Passive Stylus with Zebra logo 5" length Heavy duty - made from stainless steel and brass. No plastic parts - real pen feel. Can be used in rain. Micro-Knit Hybrid Mesh Fiber Tip provides silent, smooth gliding use. Big improvement over rubber tipped of plastic tipped stylus. Compatible with all capacitive touch screen devices. Can be tethered to device using SG- TC5NGTC7NG-TETHR-03. 	
SG-TC5NGTC7NG-TETHR-03 (pack of 3)		Tether for Stylus	 String type tether prevents loss of stylus NOTE: This tether is recommended when using Fiber Tipped Stylus (SG- STYLUS-TCX-MTL-03). Other tethers may not fit easily through the tether loop hole on the stylus. 	

KT-TC7X-TETHR1-03 (pack of 3)	Replacement Coiled Tether for Stylus	 This tether is included with Stylus Kit with Tether (SG-TC7X-STYLUS-03) Not recommended when using Fiber Tipped Stylus (SG-STYLUS-TCX-MTL- 03). 	
SG-ET5X-SLTETR-01 (single)	Replacement Coiled Tether for Stylus	 This tether is typically used with the ET5X series' stylus. Not recommended when using Fiber Tipped Stylus (SG-STYLUS-TCX-MTL-03). 	
SG-TC8X-HDSTP-01 (single)	Handstrap	 Provides added safety against accidental drops of the device while on the move. Also provides a loop and tether point for the optional stylus. This handstrap is an optional accessory on TC8300 units. This handstrap is typically included with each TC8000 unit, so this would be a spare/replacement handstrap. 	
50-12500-066	Wrist Strap	 Convenient lanyard-style wrist strap allows users to keep hands free to perform tasks and handle objects. Attaches to bottom of TC8X's handle. 	
50-15400-031	Tool Balancer/Pulley	Used when installing Boot with D-Clip (Ultima Case # AE2449DW) on a forklift	

MISC-TC8X-SCRN-01 (pack of 5) Vehicle/Forklift Cradle	s and Holders	Screen Protectors	► High durability screen protector	
NOTE: See <u>Common I</u>			rackets used with cradles and hol	ders.
Part Number	Picture	Description	Notes	Required Items
7160-1277-01 Gamber Johnson (3rd party) * <u>http://www.gamberjohnson.</u>	com	Gamber Johnson Charge- Only Vehicle Cradle	 For use in enterprise, logistics, and material handling vehicles. Universal AMPs and NEC hole patterns for attaching Gamber-Johnson mounts, RAM mounts, and other brackets. Eliminate daily battery exchanges and device downtime by maintaining charge within your mobile work environment. Includes lock for theft deterrence. Patented slam latch technology allow single handed operation. Cable from cradle terminates with 15-pin D-sub connector. Additional pigtail cable from 15-pin D-sub to 1.7mm barrel jack connector included. Not compatible with DPM (Direct Part Mark) versions of TC8300. 	Johnson, available in inputs of 12-32VDC, 20-60VDC or 72- 110VDC Via wall outlet: ▶ Power Supply (PWR- BGA12V50W0WW and CBL- DC-388A1-01) ▶ AC Line Cord (23844-00-00F
7400-0013 (12-32 VDC input) 7400-0014 (20-60 VDC input) 7400-0015 (72-100 VDC input) Gamber Johnson (3rd party) *	com	Lind 5V Isoloated Power Supply for Gamber Johnson Charge-Only Vehicle Cradle	 Typically used when powering Gamber-Johnson Charge-Only Vehicle Cradle (7160-1277-01) from a forklift. Provides 5V DC output required by cradle. 	
various SKUs (3rd party) *		RAM Vehicle Cradles	 Spring-loaded cradle allows easy one handed insertion and removal. Compatible with RAM two-hole AMPS pattern diamond bases that will connect to B and C size ball mounts, allowing for a wide variety of mounting options. Various Cradle options: Charge-Only Charge and single USB option - single port (for Printer, Keyboards, mouse, scanners) Key Locking Heated POGO pins for operations in wet and freezing environments. The USB port will not support DS3608-ER scanner in full power mode. 	For Charging <i>RAM GDS Modular Charger</i> , see below For Mounting ▶ see RAM website for options

EMC Product Line - TC8X TAG

		Γ		T
 3PTY-RAM-GDSCABUSBADC901U (USB-A to 5.5mm DC cable only) 3PTY-RAMGDSCHARGEM55V7B1U (10-30V input range) 3PTY-RAM-GDSCHARGEM55V8BU (30-64V input range) NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with thems and conditions packaged with the products. Zebra's Limited Waranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service. See PMB 11136 for more into. 		RAM GDS Modular Charger	 Used to power RAM Vehicle Cradles Charger includes: USB Type-A male connection to 5.5mm DC connector adapter cable Hard wired power adapter, USB Type-A female connector; 10-30V or 30-64V input range, 5V output Eases device upgrades by avoiding rewiring, just unplug power connector and attach new charger components 	
various SKUs (3rd party) * https://www.rammount.com Un-Powered Cradles and Hold	ders (passive holders, no char	RAM GDS Modular Chargers	 Used to power RAM Vehicle Cradles Chargers includes: USB Type-A male connection to 5.5mm DC connector adapter cable Hard wired power adapter, USB Type-A female connector; 10-30V or 30V-64V input range, 5V output When upgrading devices, avoid rewiring by unplugging power connector and attaching new charger components 	
Part Number	Picture	Description	Notes	Required Items
MNT-TC8X-FMKT6-01 (with 6" pedestal arm) MNT-TC8X-FMKT8-01 (with 8" pedestal arm)	\$ls	Fork Lift Cradle with Swivel Lock KIT (un-powered)	 Holds TC8X for convenient mounting on fork lift when not in use. Spring loaded design allows for quick insertion and removal from cradle. Installs on a roll bar or square surface of the forklift. Features swivel lock feature allowing the cradle to be easily rotated and locked in place for using the TC8X in landscape or portrait mode. Cradle also features vibration damper to protect the device under extreme shock and vibration conditions. Does NOT charge TC8X Kit includes the following: Fork Lift Cradle, Extreme Duty with Swivel Lock (MNT-TC8X-FLCH-01) Proclip Clamp Mount (3PTY-PCLIP- 215677) Proclip Pedestal Arm with 90° Offset (6" long Arm 3PTY-PCLIP-215885 used on MNT-TC8X-FMKT6-01) (8" 	

MNT-TC8X-FH-01	Fork Lift Cradle, fixed position (un-powered)	 Holds TC8X for convenient mounting on fork lift when not in use. Spring loaded design allows for quick insertion and removal from cradle. Cradle can be rotated for using the TC8X in landscape or portrait mode by rotating from the cradle clamp mount used to attach to vehicle. Does NOT charge TC8X. Mount ready via AMPS hole patterm Uses ProClip Spring Loaded Holder (510874). Not compatible with DPM (Direct Part Mark) versions of TC8300. 	Typically used with ProClip Forklift/Vehicle Cradle Clamp Mount - for square frame mounting (3PTY-PCLIP- 241478). Can be ordered as a kit which includes this clamp mount.
MNT-TC8X-FHKT-01	Fork Lift Cradle, fixed position KIT (un-powered)	 Holds TC8X for convenient mounting on fork lift when not in use. Spring loaded design allows for quick insertion and removal from cradle. Cradle can be rotated for using the TC8X in landscape or portrait mode by rotating from the cradle clamp mount used to attach to vehicle. Installs on a roll bar or square surface of the forklift and allows the device to be used in landscape or portrait mode by rotating the cradle from the clamp mount. Does NOT charge TC8X Kit includes the following: Fork Lift Cradle, Standard Duty, fixed position (MNT-TC8X-FH-01) Proclip Clamp Mount (3PTY- PCLIP-241478) Uses ProClip Spring Loaded Holder (510874). Not compatible with DPM (Direct Part Mark) versions of TC8300. 	

				_
various (3rd party) * http://www.proclipusa.com/cate	egory/zebra	Additional Vehicle Cradles (un-powered)	 Holds TC8X for convenient mounting on vehicles / fork lifts when not in use. Versions available with these features: Fixed Mount or Tilt & Swivel With or without vibration damper With or without top support for securely holding device in cradle. Mount ready via AMPS hole pattern. 	Mount on vehicle using ProClip Pedestal or Forklift Mount
various (3rd party) * <u>https://www.rammount.com</u>		RAM Vehicle Holders	 Spring-loaded cradle allows easy one handed insertion and removal. Various SKUs available that include different mounting brackets. 	
7160-1277 Gamber Johnson (3rd party) * <u>http://www.gamberjohnson.com</u>		Gamber Johnson Forklift Holder (un-powered)	 For use in enterprise, logistics, and material handling vehicles. Universal AMPs and NEC hole patterns for attaching Gamber-Johnson mounts, RAM mounts, and other brackets. Includes lock for theft deterrence. Patented slam latch technology allows single handed operation. Not compatible with DPM (Direct Part Mark) versions of TC8300. 	
Headset/Audio Accessories				
Wired Headsets and Audio NOTE: Snap-On Audio adapter re		ets on all TC8X series devices -	see <u>Snap-On Accessories</u> section above	
Part Number	Picture	Description	Notes	Required Items

HDST-35MM-PTT1-02	PTT and VoIP Headset (3.5mm Standard jack)	 For Push-To-Talk (PTT) and VoIP telephony Uses standard 3.5mm jack. Rotating earpiece allows for right or left ear configuration Built-in cord wrap mono with microphone includes clip for attaching PTT button to clothing. NOTE: Use of Locking connector headset (HDST-35MM-PTVP-02) is recommended. Improved resistance to cleaning and sanitizing products vs. HDST-35MM-PTT1-01 	3.5mm Snap-on Audio Adapter (CBL-TC8X-AUDBJ- 01)
3PTY-NO-EHL1W-01	PTT and VoIP Headset, over the ear (3.5mm Standard jack)	 For Push-To-Talk (PTT) and VoIP telephony. Compatible with Zebra PTT Express and PTT Pro. Uses standard 3.5mm jack. Speaker fits over the ear vs. HDST-35MM-PTT1-02 Rotating earpiece allows for right or left ear configuration mono with microphone includes clip for attaching PTT button to clothing. 	
HDST-35MM-PTVP-02	PTT Headset (3.5mm Locking jack)	 For Push-To-Talk (PTT) and VoIP telephony Uses 3.5mm rugged jack that is keyed/collared for a locking failsafe connection. Rotating earpiece allows for right or left ear configuration Built-in cord wrap mono with microphone includes clip for attaching PTT button to clothing. Improved resistance to cleaning and sanitizing products vs. HDST-35MM-PTVP-01 	3.5mm Snap-on Audio Adapter (CBL-TC8X-AUDBJ- 01)
HS2100-OTH	HS2100 Rugged Wired Headset (Over the Head headband)	 Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzero temperatures Feather-light for extraordinary comfort Noise cancellation for a superior voice experience in the noisiest environments Detachable swivel boom minimizes costs. Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. User-replaceable pads and windscreens maximize comfort and hygiene 	(1) HS2100 to 3.5mm Standard Cable (CBL-HS2100- 3MS1-01) AND TC8X to 3.5mm Snap-On Adapter (CBI -TC8X-AUDB-I-01)

HS2100-BTN-L	6	HS2100 Rugged Wired Headset (Behind the Neck Left headband)	 Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzero temperatures Feather-light for extraordinary comfort Noise cancellation for a superior voice experience in the noisiest environments Detachable swivel boom minimizes costs. Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. User-replaceable pads and windscreens maximize comfort and hygiene 	Requires one of the following cable options: (1) HS2100 to 3.5mm Standard Cable (CBL-HS2100- 3MS1-01) AND TC8X to 3.5mm Snap-On Adapter (CBL-TC8X-AUDBJ-01) OR (2) Quick Disconnect Headset cable (CBL-HS2100-QDC1-02) AND TC8X to Quick Disconnect Adapter Cable (CBL-TC8X-AUDQD-01) See HS2100/HS3100 Accessories Document for additional headset accessories
VR12 (3rd party) * <u>http://www.blueparrott.com</u>		BlueParrott VR12 Wired Noise Cancelling Headset	 Audio accuracy for voice picking and other speech recognition applications. High quality durability stands up to all-day, every-day use. Lightweight design is easy and comfortable to wear all day. Compatible with most major wearable computers and devices used in voice-picking environments. G type (GN Netcom) Quick Disconnect. Convertible design gives choice of over-the-head and behind-the-neck wearing styles. 	Quick-Disconnect Snap-on Audio Adapter (CBL-TC8X- AUDQD-01)
CBL-HS2100-3MS1-01	N/	HS2100 Headset Standard Cable (3.5 mm jack)	 3.5mm barrel jack connector For use with TC7X, TC8X, or other devices using a 3.5mm barrel jack audio connector Cable is 43" (1.1 M) long Rugged cable with rugged connectors that are collared/keyed for failsafe connectivity. 	3.5mm Snap-on Audio Adapter (CBL-TC8X-AUDBJ- 01)
CBL-HS2100-QDC1-02	Or	HS2100 Quick Disconnect Cable	 For use when connecting HS2100 to devices using standard Quick Disconnect jack. Cable length is approximately 33" (84 cm). Has improved quick disconnect connector and strain relief vs. CBL-HS2100-QDC1-01. 	TC8X to Quick Disconnect Adapter Cable (CBL-TC8X- AUDQD-01)
ADP-35M-QDCBL1-01	\bigcirc	RCH50/RCH51 Headset Adapter Cable	 Connects RCH50/RCH51 headset (or headsets with Quick-Disconnect connector) to devices with 3-pole 3.5mm barrel jack connector. Cable features a rugged keyed/collared jack for a locking failsafe connection. Recommend using Quick-Disconnect Snap-On Audio Adapter (CBL-TC8X-AUDQD-01) instead. 	3.5mm Snap-on Audio Adapter (CBL-TC8X-AUDBJ- 01)

ADP-LOCK-3.5HT1-01		Spare/Replacement 3.5mm Audio Adapter Retention and Anti-Rotation Lock	 This clip is used with the Snap-on 3.5mm Audio Adapter (CBL-TC8X- AUDBJ-01) and keyed headset cables to prevent cable rotation/spinning and also to provide a secure, reliable headset connection. Clip is normally included with the Snap on Adapter, this is a spare/replacement clip/lock. NOTE: This is a Spare/Service Parts item. Order by contacting Zebra Support Center - see SMB 6233 for details. 	
Bluetooth Headsets and A NOTE: Bluetooth headsets with PTT		FExpress application. Check with Eng	ineering to verify compatibility with Zebra PTT Pro	application.
Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetooth Headset for VDP applications	 HD Voice, also known as Wide Band Audio, brings incredible audio clarity Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzerce temperatures Feather-light for extraordinary comfort Noise cancellation tuned for VDP (voice directed picking) applications. Not designed for the agressive noise cancellation required for VoIP or voice calls. Headset's send level is not tuned to satisfy VoIP or voice standards and will result with audio being quieter at the far end and delivering more noise. Swap batteries on the fly — without losing the Bluetooth connection Split-second tap-to-pair simplicity using NFC. Detachable swivel boom minimizes costs. Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. User-replaceable pads and windscreens maximize comfort and hygiene 15 hours of battery power 	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * <u>http://www.blueparrott.com</u>		BlueParrott Bluetooth Headsets	 Various Bluetooth models available with options that include: Blocking out 96% of background noise Over 24 hours of talk time NFC Tap to Pair capable Bluetooth wireless range capable up to 300 ft. Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options. 	

	(Dina di		talkie style Push-to-Talk applications, including Zebra PTT Pro (check with	
APTT1 or APTT2 (3rd party) *		Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	Zebra PTT Pro engineering team for current device/OS support). Includes clip for attaching device to closthing for lapel speaker/mic usage. Features several buttons which the application developers can assign to different functions. Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. Device is ruggedized, MIL-STD 810G and IP67. Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port.	
https://www.aina-wireless.com/			 Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. Can be easily paired to mobile computer using NFC tap-to-pair. 	
BTR-155 (3rd party) *		Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	 Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). Includes clip for attaching device to closthing for lapel speaker/mic usage. Rugged wireless speaker microphone IP55. Allows cable-free movement Familiar speaker microphone functions; PTT and volume buttons Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. LED status indication High speaker volume Includes: Savox RSM Modular Wired earpiece Wall Charger USB Cable Quick Start Guide Carrying Strap 	
various (3rd party) * <u>http://stonemountainltd.com</u>		Stone Mountain BluSkye Bluetooth Remote Speaker Mic (RSM)	 Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). Device is ruggedized, MIL-STD 810G and IP68. 	
Power Cords/Power Supplies				
Power Cords/Power Supp				

CBL-DC-388A1-01		DC Power Cord	 ► Used along with Power Supply PWR- BGA12V50W0WW to power Single Device ShareCradles and 4-Slot Battery Charger. ► Cable length is 1.8 meters 	
PWR-BGA12V50W0WW	A STATE OF	Power Supply	 Used to power Single Device ShareCradles and 4-Slot Battery Charger. 100-240 VAC,12V, 4.16A, 50W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-148R 	 ▶DC Line Cord (CBL-DC- 388A1-01) ▶AC Line Cord (23844-00-00F or country specific version)
KIT-PWR-12V50W		Power Supply Kit	► Includes Power Supply (PWR- BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01)	► AC Line Cord (23844-00-00F or country specific version)
CBL-DC-383A1-01		DC Line Cord	 ► Used to power Snap-On USB/Charge Cable with Power Supply PWR- BUA5V16W0WW ► Cable length is 6 ft. 	
PWR-BUA5V16W0WW		Power Supply	 ► Used with Snap-On USB/Charge Cable ► 100-240VAC, 5.4V, 3A, 16W ► Meets US DOE Level VI efficiency standard ► Replaces PWRS-14000-249R 	DC Line Cord (CBL-DC-383A1- 01) and AC Line Cord (50-16000- 182R)
CBL-DC-381A1-01		DC Power Cord	 Used to power Multi-Device ShareCradles when using Level VI Efficiency power supply (PWR- BGA12V108W0WW) Unlike CBL-DC-382A1-01, this cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles. 	
CBL-DC-382A1-01	S.	DC Power Cord	►Used to power Multi-Device ShareCradles when using Level VI Efficiency power supply (PWR- BGA12V108W0WW).	
CBL-DC-523A1-01	10	2-Way DC Y Power Cord	►Used to power two 4-Slot Battery Chargers with one Power Supply (PWR- BGA12V108W0WW)	
PWR-BGA12V108W0WW		Power Supply	 Used to power Multi-Device ShareCradles 100-240 VAC, 12V, 9A, 108W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-241 R 	 ▶ DC Line Cord (CBL-DC- 382A1-01 or CBL-DC-523A1- 01) ▶ AC Line Cord (23844-00-00F or country specific version)

23844-00-00R	¢.	AC Line Cord	 ► Used with power supplies listed above. ► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries. 	
50-16000-182R	*0	AC Line Cord	► Used with PWRS-14000-249R/PWR- BUA5V16W0WW to power Snap-on charging cables. ► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries.	
Batteries				
Part Number	Picture	Description	Notes	Required Items
BTRY-TC8X-70MA1-01 (single) BTRY-TC8X-70MA1-10 (10 pack) BTRY-TC8X-70MA1-IN (for use in India - single)		TC8X Spare Battery with PowerPrecision+ (7000 mAh)	 All TC8300 units originally ship with this battery. Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). 	