

## **Technical Accessory Guides (TAGs)**

For Associates, Resellers, ISVs and Alliance Partners
Global



Version: Active-Only
Will only show products that are known to be available for sale

Need to provide an update or change? Contact <a href="mailto:pgw786@zebra.com">mailto:pgw786@zebra.com</a>







## MC2200/MC2700 Series Technical Accessory Guide



Does NOT include accessories for MC2100 series. See separate guide for MC2100 series accessories.

NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.

\* Zebra does not endorse or specifically recommend any third-party products, accessories, or hardware. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

## **Cradles and Charging**

Cradles				
Part Number	Picture	Description	Notes	Required Items
CRD-MC2X-2SUCHG-01		Single Slot USB/Charging Cradle	▶ Connects to USB-C port and 2-pin charge contacts on bottom of device. ▶ Supports fast-charging of MC2200/MC2700 device and spare battery. Charges Standard Capacity battery, including spare battery, from 0-90% in less than 3 hours. Charges Extended Capacity battery, including spare battery, from 0-90% in about 4.5 hours. ▶ LED notification of spare battery charging status. ▶ Compatible with devices with hand strap or Trigger Handle attached. ▶ Optional USB to Ethernet Module (MOD-MT2-EU1-01) can be used to convert to Ethernet enabled cradle. ▶ Does not use Zebra ShareCradle design.	BGA12V50W0WW ►DC Line Cord (CBL-DC-
KIT-MC2X-CHGPWR-01		Single Slot USB/Charging Cradle KIT	► Kit includes: - Single Slot USB/Charging Cradle (CRD-MC2X-2SUCHG-01) - Standard Capacity Spare Battery (BTRY-MC2X-35MA-01) - Power Supply (PWR- BGA12V50W0WW - DC Line Cord (CBL-DC-388A1-01)	►AC Line Cord (23844-00-00F or country specific version)  ►USB Cable (25-124330-01R) for PC connection
MOD-MT2-EU1-01		USB to Ethernet Module	► Attaches to Single Slot USB/Charge Cradle (CRD-MC2X-2SUCHG-01) to provide Ethernet support  ► Mechanical switch selects between USB B port and RJ45 Ethernet jack.  ► 10/100/1000 Mbps speed  ► LEDs on module indicate connectivity and speed.	Single Slot USB/Charge Cradle (CRD-MC2X-2SUCHG- 01)

NOTE: Items highlighted in grey may not be orderable/available

	1		<u> </u>	
CRD-MC2X-1SCU-01		Single Slot Base USB/Charging Cradle	► Connects to USB-C connector on bottom of device.	►USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
CRD-MC2X-5SCHG-01	TITITITI	5-Slot Charge-Only ShareCradle	▶ Will charge up to five devices. ▶ Charges Standard Capacity battery from 0-90% in less than 3 hours. Charges Extended Capacity battery from 0-90% in about 4.5 hours. ▶ Connects to 2-pin Charge Connectors on bottom of device. ▶ Compatible with devices with hand strap or Trigger Handle attached. ▶ Does not charge spare batteries ▶ Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01).	► Power Supply (PWR-BGA12V108W0WW) ► DC Line Cord (CBL-DC-381A1-01) ► AC Line Cord (23844-00-00F or country specific version)
CRD-MC2X-4SC4BC-01		4-Slot Charge-Only ShareCradle with Spare Battery Charging	▶ Will charge up to four devices and four spare batteries. ▶ Charges Standard Capacity battery, including spare battery, from 0-90% in less than 3 hours. Charges Extended Capacity battery, including spare battery, from 0-90% in about 4.5 hours. ▶ Connects to 2-pin Charge Connectors on bottom of device. ▶ Compatible with devices with hand strap or Trigger Handle attached. ▶ Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01).	► Power Supply (PWR-BGA12V108W0WW) ► DC Line Cord (CBL-DC-381A1-01) ► AC Line Cord (23844-00-00F or country specific version)
BRKT-SCRD-SMRK-01		5-Slot ShareCradle Mounting Bracket	➤ Allows for rack and wall mounting of one 5-Slot ShareCradle or up to four 4-Slot Spare Battery Chargers.  ► Bracket can be mounted on standard 19" network rack or on a wall.  ► Has cable routing slots and removable power supply tray that stores and conceals power supplies.  ► Adjustable tabs & screw mounts for easy hanging/installation.  ► Adjustable orientations:  - 25° High Density (5-Slot Charge Only Cradle)  - Horizontal (Single Slot Cradle or 4-Slot Battery Chargers)  ► See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket.	

ļ				
ADP-TC7X-PLT-FX		5-Slot ShareCradle Mounting Bracket Adapter Plate for Honeywell	► Allows Zebra Multi-Slot ShareCradles to be mounted on legacy Honeywell Flex Cradle Wall Mount Brackets (HON SKU #203-641-002).  ► Includes hardware to attach plate to HON wall bracket and secure ShareCradle to plate.  ► NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
Battery Charging				
Part Number	Picture	Description	Notes	Required Items
SAC-MC2X-4SCHG-01		4-Slot Spare Battery Charger	► Charges up to four spare batteries. ► Standard Capacity batteries will charge from 0-90% in less than 3 hours. Charges Extended Capacity from 0-90% in about 4.5 hours. ► Can be used standalone or up to 4 Chargers can be mounted on Mounting Bracket (BRKT-SCRD-SMRK-01)	To power a single Charger  ▶ Power Supply (PWR- BGA12V50W0WW)  ▶ DC Line Cord (CBL-DC-388A1- 01)  ▶ AC Line Cord (23844-00-00R or country specific version)  To power two Chargers  ▶ Power Supply (PWR- BGA12V108W0WW)  ▶ DC Y-Cable Line Cord (CBL-DC- 523A1-01)  ▶ AC Line Cord (23844-00-00R or country specific version)
KIT-MC2X-BTRYPWR-01		4-Slot Spare Battery Charger with Batteries KIT	► Kit includes: - 4-Slot Spare Battery Charger (SAC-MC2X-4SCHG-01) - QTY 4 Standard Capacity Spare Battery (BTRY-MC2X-35MA-01)	To power a single Charger  ▶ Power Supply (PWR- BGA12V50W0WW)  ▶ DC Line Cord (CBL-DC-388A1- 01)  ▶ AC Line Cord (23844-00-00R or country specific version)  To power two Chargers  ▶ Power Supply (PWR- BGA12V108W0WW)  ▶ DC Y-Cable Line Cord (CBL-DC- 523A1-01)  ▶ AC Line Cord (23844-00-00R or country specific version)
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01 or CBL-TC2Y-USBC90A-01		USB-C cable for Charging/Communication	▶ USB-A to USB-C cable ▶ Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge/Communication Cradle (CRD-MC2X-BS1CO-01). ▶ Can be used to charge the device via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ▶ Cable length is 1M (~3.3 ft.) ▶ Will charge battery in device from 0 to 90% in less than 3 hours using the wall-adapter 5V power supply or Cigarette Adapter. ▶ Can also be used to communicate with device without using a Cradle. ▶ CBL-TC2Y-USBC90A-01 features USB-A connector with a 90° bend allowing cable to be used in tighter locations. Cable length is about 1.1M (45").	For charging via AC Wall Outlet: USB Power Adapter (PWR- WUA5V12W0US - or country specific version)

3rd party *		USB-C cable for Charging/Communication	▶ USB-A to USB-C cable ▶ Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge/Communication Cradle (CRD-MC2X-BS1CO-01). ▶ Can be used to charge the device via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ▶ Will charge battery in device from 0 to 90% in less than 3 hours using the wall-adapter 5V power supply or Cigarette Adapter. ▶ Can also be used to communicate with device without using a Cradle.	For charging via AC Wall Outlet: USB Power Adapter (PWR- WUA5V12W0US - or country specific version) For charging in-vehicle:
Communication Cables				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01	~ <b>Q</b>	USB-C cable for Charging/Communication	▶ USB-A to USB-C cable ▶ Attaches to USB-C port on the bottom of the device. ▶ Can be used to charge the device via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ▶ Cable length is 1M (~3.3 ft.) ▶ Will charge battery in device from 0 to 90% in less than 3 hours using the wall-adapter 5V power supply or Cigarette Adapter. ▶ Can also be used to communicate with device without using a Cradle.	For charging via AC Wall Outlet: USB Power Adapter (PWR- WUA5V12W0US - or country specific version) For charging in-vehicle: USB Cigarette Lighter Adapter (CHG-AUTO-USB1-01)
3rd party *		USB-C cable for Charging/Communication	adapter) ▶ Will charge battery in device from 0 to 90% in less than 3 hours using the wall-adapter 5V power supply or Cigarette	USB Power Adapter (PWR- WUA5V12W0US - or country specific version)
25-124330-01R	O	Single Slot Cradle to PC/Host USB cable	► Used with Single Slot Base USB/Charging Cradle with Spare Battery Charging (CRD-MC2X-2SUCHG- 01) ► Micro USB connection on cradle end	
3rd party *  (see http://www.cyberguys.com	n/product-details/?productid=:	USB micro-A to USB A Female adapter	► Allows the MC2200/MC2700 to act as a USB host to connect to devices like USB flash drives/memory sticks, mice, etc.  ► Connects to Single Slot Base USB/Charging Cradle with Spare Battery Charging (CRD-MC2X-2SUCHG-01).	

Part Number	Picture	Description	Notes	Required Items		
TRG-MC2X-SNP1-01		Trigger Handle	▶ Trigger Handle accessory offers customers the option of using the product in a gun form factor, ideal for scan-intensive situations. ▶ Easily attaches to MC2200/MC2700 top housing ▶ Easily removed to access battery ▶ Integrated 3-point stand for resting terminal when not in use ▶ Connects to I/O connector on rear of device. ▶ Can be used with optional Wrist Tether Strap (50-12500-066) or Handstrap for Gun Configuration (SG-MC2X-HSTRP2-02). ▶ Does not block view of rear facing camera and is compatible with standard and extended capacity batteries.			
KIT-MC2X-ENBNDLE-01		Trigger Handle KIT	► Kit includes: - Trigger Handle (TRG-MC2X-SNP1-01) - Wrist Strap for Trigger Handle (SG-MC2X-HSTRPH-01) - Screen Protector (MISC-MC2X-SCRNPT-01)			
KIT-MC2X-CPRTCT-01	70	Trigger Handle Protection KIT	►Kit includes: - Trigger Handle (TRG-MC2X-SNP1-01) - Boot for Trigger Handle Configuration (SG-MC2X-RBH2-01) - Screen Protector (MISC-MC2X-SCRNPT-01)			
	Soft Goods - Cases/Holsters					
Part Number	Picture	Description	Notes	Required Items		
SG-MC2X-HSTRP-01		Handstrap	► This is a spare/replacement handstrap. Handstrap is typically included with each device.     ► Strap attaches to back of device.     ► Nylon and Hypalon Pad provides maximum comfort and wear resistance.     ► Adjustable Velcro design accomodates various hand sizes.     ► Not compatible with Snap-on accessories (Trigger Handle).     ► Compatible with devices using Standard or Extended Capacity battery.			

SG-MC2X-HSTRPH-01		Handstrap for Trigger Handle configuration	► This is an optional handstrap for devices with the Trigger Handle attached.     ► Strap attaches to the bottom of device and to bottom of Trigger Handle ► Nylon and Hypalon Pad provides maximum comfort and wear resistance.     ► Only compatible with devices using Snap-on Trigger Handle.     ► Can be used with devices using Standard or Extended Capacity battery.	
SG-MC2X-HLSTR-01	WESTERN STATE OF THE STATE OF T	Soft Holster for Brick configuration	▶ Vertical orientation with Open Bucket design with strap to secure device in holster while still allowing for easy insertion and removal. ▶ Holster can be worn on belt or crossbody using Shoulder Strap (58-40000-007R). ▶ Non rotating for maximum durability. ▶ Opening at bottom of holster for providing drainage and route for audio from device's speaker. ▶ Compatible with devices with or without Boot attached. ▶ Not compatible with devices with Trigger Handle attached.	
SG-MC3021212-01R	00	Fabric Holster for Gun configuration	▶ Only compatible with devices with Snap-on Trigger Handle attached. ▶ Compatible with devices with or without Boot attached. ▶ This is the same holster used with MC3X series. ▶ Can be mounted on belt or includes tether points to be used with Universal Shoulder Strap (58-40000-007R)	
SG-MC2X-RB1-01		Rubber Boot for Brick Configuration	▶ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ▶ Compatible with holster (SG-MC2X-HLSTR-01). ▶ Not compatible with devices with Trigger Handle attached. ▶ Boot must be "peeled back" or removed before inserting into cradles.	

KIT-MC2X-TPRTCT-01		Boot Protection KIT for Brick Configuration	► Kit includes: - Boot for Brick Configuration (SG-MC2X-RB1-01) - Hand Strap (SG-MC2X-HSTRP-01) - Screen Protector (MISC-MC2X-SCRNPT-01)	
SG-MC2X-RBH2-01		Boot for Trigger Handle Configuration	▶ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ▶ Compatible with holster (SG-MC3021212-01R). ▶ Boot must be "peeled back" or removed before inserting into cradles.	
58-40000-007R	S	Universal Shoulder Strap	▶1.5" wide, 22 to 50" max. length	
A1236ST (3rd party) * https://www.shilpitrading.com	S	Universal Shoulder Strap	➤ Belt is 1 inch wide ➤ Extends to 54 inches ➤ Moulded shoulder pad ➤ Plastic swivel snap hooks	
11-08062-02R	S	Belt for holster	► Belt is 2 inches wide ► Extends to 48 inches ► Has improved buckle and softer belt material	
V6198DW (3rd party) * http://www.ultimacase.com	<b>E</b>	Belt Extender	► Used to extend the holster belt (11- 08062-02R) an additional 10 inches	
50-12500-066	W	Wrist Strap for Trigger Handle	► Attaches to bottom of Snap-on Trigger Handle (TRG-MC2X-SNP1-01)	
Misc				
Part Number	Picture	Description	Notes	Required Items

SG-STYLUS-TCX-MTL-03 (pack of 3)	amus and a second	Fiber Tipped Stylus	<ul> <li>▶ Black Passive Stylus with Zebra logo</li> <li>▶ 5" length</li> <li>▶ Heavy duty - made from stainless steel and brass. No plastic parts - real pen feel.</li> <li>▶ Can be used in rain.</li> <li>▶ Micro-Knit Hybrid Mesh Fiber Tip provides silent, smooth gliding use.</li> <li>▶ Big improvement over rubber tipped o plastic tipped stylus.</li> <li>▶ Compatible with all capacitive touch screen devices.</li> <li>▶ Can be tethered to handstrap on device using SG-TC5NGTC7NG-TETHR-03.</li> </ul>		
Other Stylus		Rubber or Plastic Stylus	► Not supported - Stylus Mode is NOT supported on the MC2200/MC2700. ► Hard Plastic/Rubber stylus such as SG-TC7X-STYLUS-03 will not work. ► Fiber Tipped Stylus (SG-STYLUS-TCX MTL-03) will work - does not require Stylus Mode on device.		
SG-TC5NGTC7NG-TETHR-03 (pack of 3)		Tether for Stylus	► String type tether prevents loss of stylus ► NOTE: This tether is recommended when using Fiber Tipped Stylus (SG-STYLUS-TCX-MTL-03). Other tethers may not fit easily through the tether loop hole on the stylus.		
MISC-MC2X-SCRNPT-01 (pack of 5)		Screen Protector	▶ Tempered glass screen protector to provide an extra layer of ruggedness to the Gorilla Glass touch screen of the device. ▶ Provides an oleophobic layer to disperse finger oils.		
Wired Headsets and Audio	Headset/Audio Accessories  Wired Headsets and Audio Accessories  NOTE: MC2200/MC2700 does not have a headset jack. Use a USB-C or Bluetooth headset instead.				

EMC Product Line - MC22000/MC2700 TAG Document Update date: 6/21/23

Part Number	Picture	Description	Notes	Required Items
3rd party *		USB-C Headsets	<ul> <li>▶ Headset connects via the bottom USI C connector on device.</li> <li>▶ Must be Google certified USB-C headset.</li> </ul>	
	and Audio Accessories ith PTT function not supported		a WFC Central Client app Release Notes to verify comp	atibility.
Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetoot Headset for VDP application		See HS2100/HS3100 Accessories Document for headset accessories

various Bluetooth models B550-XT B350-XT

C400-XT C300-XT

(3rd party) \*

http://www.blueparrott.com



BlueParrott Bluetooth Headsets ► Various Bluetooth models available with options that include:
- Blocking out 96% of background

- Blocking out 96% of backgroun noise
- Over 24 hours of talk time

comfort and hygiene

▶ 15 hours of battery power

- NFC Tap to Pair capable
- Bluetooth wireless range capable up to 300 ft.
- Convertible wearing options: over the head, behind the neck.

See BlueParrot site for model specific options.

Document Update date: 6/21/23

APTT1 (3rd party) *  https://www.aina-wireless.com/	C D C D C D C D C D C D C D C D C D C D	Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶ Features several buttons which the application developers can assign to different functions. ▶ Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ▶ Device is ruggedized, MIL-STD 810G and IP67. ▶ Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ▶ Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ Can be easily paired to mobile computer using NFC tap-to-pair.	
BTR-155 (3rd party) *		Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶ Rugged wireless speaker microphone IP55. ▶ Allows cable-free movement ▶ Familiar speaker microphone functions; PTT and volume buttons ▶ Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ LED status indication ▶ High speaker volume ▶ Includes: - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap	
various (3rd party) *  http://stonemountainltd.com		Stone Mountain BluSkye Bluetooth Remote Speaker Mic (RSM)	▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Device is ruggedized, MIL-STD 810G and IP68.	
Power Cords/Power Sup	plies			
Part Number	Picture	Description	Notes	Required Items

			► Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot	
CBL-DC-388A1-01		DC Power Cord	Base USB/Charging Cradle with Spare Battery Charging (CRD-MC2X-SE1ET-01) or 4-Slot Battery Charger (SAC-MC2X-4SCHG-01).  ▶ Cable length is 1.8 meters	
PWR-BGA12V50W0WW	The second secon	Power Supply	▶ Used to power Single Slot Base USB/Charging Cradle with Spare Battery Charging (CRD-MC2X-SE1ET- 01) or 4-Slot Battery Charger (SAC- MC2X-4SCHG-01). ▶ 100-240 VAC,12V, 4.16A, 50W ▶ Provides US DOE Level VI compliance for power efficiency. ▶ Replaces PWRS-14000-148R	►DC Line Cord (CBL-DC-388A1-01)  ►AC Line Cord (23844-00-00F or country specific version)
CBL-DC-381A1-01		DC Power Cord	► Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) ► This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles.	
CBL-DC-382A1-01		DC Power Cord	▶ Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) ▶ Cable has black extension tab for releasing the cable from the back of the cradle. This isn't required when using Multi-Slot ShareCradles. ▶ CBL-DC-381A1-01 is the preferred cable to use with MC22/MC27 cradles.	
PWR-BGA12V108W0WW	NAME AND ADDRESS OF THE PARTY O	Power Supply	► Replaces PWRS-14000-241R ► Used to power 5-Slot ShareCradles ► 9A, 108W ► Level VI Efficiency rated	►DC Power Cord (CBL-DC-382A1-01)  ►AC Line Cord (23844-00-00F or country specific version)
23844-00-00R		AC Line Cord	► Used to power with Power Supplies ► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries.	
PWR-WUA5V12W0US (US plug style) PWR-WUA5V12W0GB (UK plug style) PWR-WUA5V12W0EU (EU plug style) PWR-WUA5V12W0AU (Australia plug style) PWR-WUA5V12W0CN (China plug style) PWR-WUA5V12W0IN (India plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0BR (Brazil plug style) PWR-WUA5V12W0BR (Brazil plug style) PWR-WUA5V12W0LA (Argentina/Chile/Mexico plug styles)		USB Power Supply	▶ Used with USB-C Cable to provide a lower cost charging solution than using a Cradle. ▶ Also used to power Single Slot Charge/Communication Base Cradle (CRD-MC2X-1SCU-01). ▶ Provides higher current (2.5A) for faster charging ▶ 100-240 VAC, 5 V, 2.5 A	►USB-C Cable (CBL-TC5X- USBC2A-01 OR CBL-TC2X- USBC-01)

CHG-AUTO-USB1-01 CHG-AUTO-USB1-BR (for Brazil)		USB Cigarette Lighter Adapter	► Used with USB-C Cable to provide invehicle charging.     Includes two USB A ports providing higher current (2.5A) for faster charging	►USB-C Cable (CBL-TC5X- USBC2A-01 OR CBL-TC2X- USBC-01)
Batteries				
Part Number	Picture	Description	Notes	Required Items
BTRY-MC2X-35MA-01 (single) BTRY-MC2X-35MA-10 (pack of 10) BTRY-MC2X-35MA-BR (for use in Brazil) BTRY-MC2X-35MA-IN (for use in India)		Standard Capacity Spare Battery with PowerPrecision (3500 mAh)		
BTRY-MC2X-49MA-01 (single) BTRY-MC2X-49MA-10 (pack of 10) BTRY-MC2X-49MA-BR (for use in Brazil)	*	Extended Capacity Spare Battery with PowerPrecision (4900 mAh)	▶Battery+ icon on battery differentiates from Standard Capacity battery	

BTRY-MC2X-49MA-IN (for use in India)